April 5, 2004

Commissioner for Patents P.O. Box 1450 Alexandria, VA 22313-1450

Fr: George O. Saile, Reg. No. 19,572 28 Davis Avenue Poughkeepsie, N.Y. 12603

Subject:

Serial No. 10/790,579 03/01/04

Peter Lee et al.

ARRAY ARCHITECTURE AND PROCESS FLOW OF NONVOLATILE MEMORY DEVICES FOR MASS STORAGE APPLICATIONS

INFORMATION DISCLOSURE STATEMENT

Enclosed is Form PTO-1449, Information Disclosure Citation
In An Application.

The following Patents and/or Publications are submitted to comply with the duty of disclosure under CFR 1.97-1.99 and 37 CFR 1.56.

CERTIFICATE OF MAILING

I hereby certify that this correspondence is being deposited with the United States Postal Service as first class mail in an envelope addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450, on April), 2004.

Stephen B. Ackerman, Reg.# 37761

Signature/Date Signature/Date

AP-99-005BB

Atwood et al., "Intel Strata Flash TM Memory Technology Overview," Intel Technology Journal, 4th quarter 1997, pp.1-12, describes a stacked gate structure in which an ETOX process is used to produce a multiple level cell to store two bit in the same memory cell.

- U.S. Patent 5,828,600 to Kato et al., "Non-Volatile Semiconductor Memory," describes a nonvolatile semiconductor memory where the cells are a MOSFET with a floating gate and have low power, high speed and reduced cell area.
- U.S. Patent 5,095,344 to Harari, "Highly Compact EPROM and Flash EEPROM Devices," discloses a highly compact flash memory device using an intelligent programming technique to allow multiple bits to be stored in each cell and an intelligent erase program to extend the useful life of each cell.
- U.S. Patent 5,029,130 to Yeh, "Single Transistor Non-Volatile Electrically Alterable Semiconductor Memory Device," discloses a single transistor electrically programmable and erasable memory cell using a split gate which allows the control gate to control a portion of the channel and the floating gate to control the remaining portion of the channel.

AP-99-005BB

U.S. Patent 5,400,279 to Momodomi et al., "Nonvolatile Semiconductor Memory Device with NAND Cell Structure," discloses a nonvolatile memory device with a NAND cell structure.

Sincerely,

Stephen B. Ackerman,

Reg. No. 37761

- 1 of 1

															ACHEMON HUMAN				
6 MFC	RAY	AT L.Z	10	Ŋ	DIS	SC	L(OSURE C	FORTATION	٧.	Applicant					0/790,579			
APR 1 5 7			()	/IY	НI	7	LI	CATION			FHOR Date		<u>e</u>	el,	al.	11/0#		······································	
APR 1	(U) suvoral shouls il nacossary)													24	<u> </u>	. uvi	··		
DX ANTHON	<u> </u>								U. S ['] .	PAT	ENT DO	CUMENT	ſS				,		
MAINT	DOCUMENT HOMBER					86	n	סאנג			xwx			CCTT	พช	Mecure		ኢ የሌሀዐਘስኘ፤ (ህጉላጋ ወንደፉ	
	5	8	2	8	6	0	0	10/27/91	r Kc	to	et	J.		365	184	185.11	10/3	0/96	
					1 1			3/21/95)aa a	domi	+		365		}5		6/93	
	i –	1	H		1 1	1	1	3/10/92		er a			~	35			,	8/88	
	- 1	1					1		\ \		-V (). <u>5</u>	6/	8168	
	5	0	4	7		3	-	7/2/91		<u>eh</u>				365	18	5	1/6	2/90	
	-	-	-	\dashv	-	-	-	-											
	-	-	\dashv		$\left - \right $	_	-				· · · · · · · · · · · · · · · · · · ·	·····		···	-				
	-	-	-	-		-	-				,					·····			
	-	-	-	_		_	-								_				
	_	_		_	-	-	-								_		<u> </u>	····	
	-		_	_		_	_												
																			
<u> </u>							1		FOREIG	N PA	TENT D	OCUME	NTS	·					
	OCCUMENT NUMBER							CX CX			אַדאנע			cms	SUBG	CL SU	YES	NO	
														-	•				
																		<u> </u>	
		\dashv	1	+	+	- -	+							•					
			- -	-	- -	- -	- -								-				
	11		L		l.				OTHER	D,O C	UMENTS	(Includin	מזט א כמ	or, Tivo.	Data, Pai	ปกอกร	Pagas. El	<u>ι</u> ε.)	
_		A-	+1	N G	00/	1		etal	"T.	+0	Str	ata 1	Fla	ده اړ	Tm	M	9144	<u>-</u>	
		٦	- ·	ل.		ا	6	et al	1000	<u>۔۔</u> کو۔	,'' Τ	+-1	7.	<u>-عد-</u>	ماء:		Tair	sua l	
		<u>`</u>	(ム	<u>, M</u>	σ.	<u></u>		× 10	97	~ ~ ~	1-17	٠٠٠		4100	<u> </u>	<u> </u>	ANDVI	
			Υ_`	١_٢	^_		6	MANTI	<u>√ (((</u>		YP.	((_	•				·		
	-								 ^									-	
																			
																		54	
EXAMIER											DATE COM	COCRED							
1																			

citation if not in conformation and not considered, Include conval this form with next communication to the configura-